

## Lubricants



## Prolong the life-time of your equipment

Frontmatec high performance food grade lubricants are ideally composed to fit the food industry and your equipment.

Our oils protect your equipment from corrosion, wear and tear and are compatible with plastics and sealings, as well as taking account for high hygiene and food safety. Oils and greases are NSF-H1 approved by the Nonfood Compounds Registration Program.

Our greases have extremely high water resistance, have excellent adherent abilities, and are formulated to refrain from dripping down or wash out, to increase your savings.

Years of experience show that lubrication is a fundamental key to a well maintained plant and extends the lifetime of your equipment. Our experienced spare part engineers are ready to define the lubricant solution that will be the fundamental key that increases your profit.

Do not hesitate to contact us for more information.

### Value for you!

- Long life-time of equipment
- Increased profit
- Secure daily operation
- Low maintenance
- Cost savings
- High food safety
- NSF-H1 approved
- No allergens



Part number	Description	Operating temperature	Size
4001242849	SLBO-E Duoplan Chain Oil	-15°C to 120°C/-5°F to 248°F	5 l
40012428497	SLBO-E Duoplan Chain Oil	-15°C to 120°C/-5°F to 248°F	20 l
4001242848	SLBO-E Duoplan Chain Oil	-15°C to 120°C/-5°F to 248°F	200 l
5000018862	SLBO-G Alternative Duoplan Chain Oil for higher temperature environments	-15°C to 120°C/-5°F to 248°F	5 l
5000018862	SLBO-G Alternative Duoplan Chain Oil for higher temperature environments	-15°C to 120°C/-5°F to 248°F	20 l
5000018862	SLBO-G Alternative Duoplan Chain Oil for higher temperature environments	-15°C to 120°C/-5°F to 248°F	200 l
400124855	SLBO-I for Ancher Chains	-10°C to 120°C/14°F to 248°F	5 l
400124853	SLBO-I for Ancher Chains	-10°C to 120°C/14°F to 248°F	20 l
4001214656	SLBO-K adhesive Chain Oil for Scalding Chamber	-10°C to 120°C/14°F to 248°F	5 l
4001214656	SLBO-K adhesive Chain Oil for Scalding Chamber	-10°C to 120°C/14°F to 248°F	20 l
4001242860	SLBO-D-LT low temperature Chain Oil with unique anti-ice adhesive	-40°C to 150°C/-40°F to 302°F	50 l
400124858	SLBO-D-LT low temperature Chain Oil with unique anti-ice adhesive	-40°C to 150°C/-40°F to 302°F	200 l
5000018894	SLBO-J-HT High viscosity Gearbox and high temperature Chain Oil	-30°C to 150°C/-22°F to 302°F	5 l
5000018894	SLBO-J-HT High viscosity Gearbox and high temperature Chain Oil	-30°C to 150°C/-22°F to 302°F	20 l
5000018895	SLBO-J-HT High viscosity Gearbox and high temperature Chain Oil	-30°C to 150°C/-22°F to 302°F	200 l
5000018856	SLBO-B high quality Air Cylinder Oil	-20°C to 120°C/-4°F to 248°F	5 l
5000018858	SLBO-B high quality Air Cylinder Oil	-20°C to 120°C/-4°F to 248°F	20 l
5000018857	SLBO-B high quality Air Cylinder Oil	-20°C to 120°C/-4°F to 248°F	200 l
500018859	SLBO-C Air Lube and Belt Oil	-15°C to 120°C/-5°F to 248°F	5 l
500018861	SLBO-C Air Lube and Belt Oil	-15°C to 120°C/-5°F to 248°F	20 l
500018860	SLBO-C Air Lube and Belt Oil	-15°C to 120°C/-5°F to 248°F	200 l
4001373612	SLBO-F-HT Gearbox Oil	-30°C to 150°C/-22°F to 302°F	5 l
500018891	SLBO-H-HT long life Gear Oil	-30°C to 150°C/-22°F to 302°F	5 l
500018893	SLBO-H-HT long life Gear Oil	-30°C to 150°C/-22°F to 302°F	20 l
500018892	SLBO-H-HT long life Gear Oil	-30°C to 150°C/-22°F to 302°F	200 l
500018897	SLBO-HQHYD-32 hydraulic Oil	-15°C to 120°C	5 l
500018899	SLBO-HQHYD-32 hydraulic Oil	-15°C to 120°C	20 l
500018898	SLBO-HQHYD-32 hydraulic Oil	-15°C to 120°C	200 l
500018847	SLBO-HQHYD-46 hydraulic Oil	-15°C to 120°C	5 l
500018849	SLBO-HQHYD-46 hydraulic Oil	-15°C to 120°C	20 l
500018848	SLBO-HQHYD-46 hydraulic Oil	-15°C to 120°C	200 l
4001328954	SLBG-A Grease for Sliding Rails and Bearings	-15°C to 130°C/5°F to 266°F	25x400 g
5000020161	SLBG-A Grease for Sliding Rails and Bearings	-15°C to 130°C/5°F to 266°F	5 kg
400124879	SLBG-A Grease for Sliding Rails and Bearings	-15°C to 130°C/5°F to 266°F	18 kg
500010306	SLBG-A Grease for Sliding Rails and Bearings	-15°C to 130°C/5°F to 266°F	50 kg
500020236	SLBG-B Grease for Handtools	-25°C to 120°C/-13°F to 248°F	1x400 g
500018951	SLBG-B Grease for Handtools	-25°C to 120°C/-13°F to 248°F	25x400 g
500018950	SLBG-B Grease for Handtools	-25°C to 120°C/-13°F to 248°F	18 kg
4001328948	SLBG-L-LT Grease for low temperature	-40°C to 140°C/40°F to 284°F	25x400 g
4001373230	SLBG-L-LT Grease for low temperature	-40°C to 140°C/40°F to 284°F	18 kg

## Contact

Central/Eastern Europe  
Phone: +49 252 185 070  
E-mail: [as.ce@frontmatec.com](mailto:as.ce@frontmatec.com)

Central/Eastern Europe, Poland  
Phone: +48 227 345 551  
E-mail: [as.ce@frontmatec.com](mailto:as.ce@frontmatec.com)

Northern Europe  
Phone: +45 36 999 099  
E-mail: [as.ne@frontmatec.com](mailto:as.ne@frontmatec.com)

Southern Europe  
Phone: +34 932 643 800  
E-mail: [as.se@frontmatec.com](mailto:as.se@frontmatec.com)

Russia  
Phone: +7 495 424 9559  
E-mail: [as.ru@frontmatec.com](mailto:as.ru@frontmatec.com)

Western Europe  
Phone: +31 886 294 000  
E-mail: [as.we@frontmatec.com](mailto:as.we@frontmatec.com)